



Balcony Railing Specifications - OSHA Compliant

Height to top plain of Top Rail	5'6" to accomodate workers on stilts
Meets Top and Mid- Rail OSHA Requirements	200 lbs at Top Rail, 150 lbs at mid rail
Toe Board built in	6" incorporated toe board
Cross Members	19.5" and 39"
Diameter of Railing	1.625" - meets OSHA Requirements

Rake Railing Specifications - OSHA Compliant

V	
Height to top plain of Top Rail	42"(+/- 3") meet OSHA Requirement
Meets Top and Mid- Rail OSHA Requirements	200 lbs at Top Rail, 150 lbs at mid rail
Toe Board built in	Not required on Stair Rake
Cross Members	19.5" Mid-Rail
Diameter of Railing	1.625'' - meets OSHA Requirements

www.ironwoodusa.com/safetyrail

F 817.701.2020

HOUSTON | P 281.209.0000 F 281.209.0067 AUSTIN P 512.973.8373 F 512.973.9919 **SAN ANTONIO** P 210.521.4808 F 210.521.7618 **DALLAS** P 817.701.2006

16684 Air Center Blvd. Houston, TX 77032 8606 Wall St. Suite 200 Austin, TX 78754 2520 N Great Southwest Pkwy. Suite 104 Grand Prairie, TX 75050

101-19